





**Tecumseh**

|                       |                                         |
|-----------------------|-----------------------------------------|
| <b>CAJN4476YHR-FZ</b> | <b>Tension FZ : 220 - 240V 1~ 50 Hz</b> |
|-----------------------|-----------------------------------------|

Les performances sont données dans les **conditions EN13215** :  
Condition Dew

Gaz aspirés : 20.0 °C  
Sous refroidissement : 3.0 K

The performance data are in **EN13215 conditions** :  
Dew Condition

Return gas : 20.0 °C  
Subcooling : 3.0 K

## 50 Hz R134a



**N°5037**

| 5   T ambience | 6   T évaporation  | (°C)   | -25  | -20  | -15  | -10  | -5   | 0    | 5    | 10   | 15   |
|----------------|--------------------|--------|------|------|------|------|------|------|------|------|------|
| <b>25</b>      | 1   P frigorifique | (Watt) | 485  | 664  | 870  | 1106 | 1371 | 1664 | 1983 | 2325 | 2688 |
|                | 2   P absorbée     | (W)    | 411  | 465  | 518  | 571  | 628  | 689  | 758  | 837  | 928  |
|                | 3   I absorbée     | (A)    | 3.93 | 4.02 | 4.14 | 4.27 | 4.44 | 4.64 | 4.89 | 5.17 | 5.51 |
|                | 4   Tc             | (°C)   | 29.8 | 31.4 | 33.1 | 35.1 | 37.4 | 39.8 | 42.6 | 45.5 | 48.7 |
| <b>32</b>      | 1   P frigorifique | (Watt) | 397  | 568  | 762  | 982  | 1227 | 1497 | 1790 | 2104 | 2435 |
|                | 2   P absorbée     | (W)    | 399  | 463  | 525  | 587  | 652  | 722  | 799  | 887  | 987  |
|                | 3   I absorbée     | (A)    | 3.81 | 3.95 | 4.11 | 4.29 | 4.50 | 4.74 | 5.02 | 5.34 | 5.71 |
|                | 4   Tc             | (°C)   | 36.5 | 37.9 | 39.5 | 41.4 | 43.5 | 45.8 | 48.4 | 51.3 | 54.3 |
| <b>43</b>      | 1   P frigorifique | (Watt) |      |      | 585  | 780  | 995  | 1229 | 1481 | 1750 |      |
|                | 2   P absorbée     | (W)    |      |      | 518  | 598  | 680  | 766  | 860  | 963  |      |
|                | 3   I absorbée     | (A)    |      |      | 4.06 | 4.31 | 4.58 | 4.89 | 5.23 | 5.61 |      |
|                | 4   Tc             | (°C)   |      |      | 49.6 | 51.2 | 53.1 | 55.3 | 57.7 | 60.3 |      |

© 2019 Tecumseh Products Company  
All rights reserved

1 = cooling capacity 2 = power input 3 = current 4 = condensing temperature 5 = ambient temperature 6 = evaporating temperature

Nota : Tecumseh se réserve le droit de modifier les informations contenues dans ce document sans préavis.

Note : Tecumseh reserves the right to change information contained in this document without notification.